Intercomp CS™ 750

APPROVALS

Measurement Canada Approved



REAR VIEW



SIDE VIEW

STANDARD FEATURES

- Digital calibration
- Adjustable, auto shut off
- 1 in LCD digital readout
- Powered by 6 D cell batteries
- Infrared remote control
- Automatic backlight

SPECIFICATIONS

Resolution:
20 bit A/D delivers more than 1 million internal counts

Controls:
Zero, On, Off, Backlight

Display:
1 in (25 mm) 5-digit LCD

Indicators:
lb/kg

Power:
(Batteries are not included) six D size disposable alkaline dry cell, 250 hours or rechargeable nickel-cadmium cell, 80 hours

Dimensions:
Control box: 8.5 L x 5 W x 4.25 in H (216 L x 127 W x 108 mm H)
Lifting eye to hook: 9.5 in (241 mm)

Enclosure:
Weatherproof extruded-aluminum case

Est. Ship Weight:
8.5 lb (4 kg)

Auto Shut-off:
Low battery, or after twenty minutes without use

Accuracy:
±0.1% of reading

Temperature:
Operating -4°F to 140°F (-20°C to 60°C)

Nominal Overload:
200% of capacity

Maximum Overload:
500% of capacity

Warranty:
One-year limited warranty

Approvals:
NTEP CC 97-135, Class III 3000d
Measurement Canada AM-5228
CE

PART NUMBER/PRICE

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
43643	CS750, 100 lb (50 kg) x 0.05 lb (0.02 kg)	9 lb	Consult
43644*	CS750, 300 lb (150 kg) x 0.1 lb (0.05 kg)	9 lb	Consult
43645*	CS750, 500 lb (250 kg) x 0.2 lb (0.1 kg)	9 lb	Consult
43646*	CS750, 1,000 lb (500 kg) x 0.5 lb (0.2 kg)	9 lb	Consult

Batteries not included

OPTIONS/ACCESSORIES

PART #	DESCRIPTION	PRICE
43939	RS-232 serial output	Consult
43941	120/220 V external charger (batteries not included) for qty 3 x 3 D-Nicad/NiMH	Consult
97447	Battery pack, qty 2 x 3 "D"-size-Nicad	Consult

**NTEP and Measurement Canada Certified*

RICE LAKE WEIGHING SYSTEMS
An ISO 9001 Registered Company © 2014 Rice Lake Weighing Systems 01/14 Prices and specifications subject to change without notice. Visit ricelake.com for current prices.